

## CLAIMS

1. A sequin feeding apparatus comprising:

a feeding mechanism for feeding a continuous sequin strip, let out  
5 from a reel and then placed on an upper surface of a supporting plate, a  
predetermined pitch at a time through forward and rearward movement of  
a feed lever, said feeding mechanism feeding the continuous sequin strip by  
causing said feed lever to move forward with a distal-end hook portion of  
said feed lever engaging a center hole of a sequin;

10 a lock lever having, at a free end thereof, an engaging claw  
engageable with a center hole of a sequin; and

a lock lever drive mechanism pivotably supporting said lock lever  
near said feed lever,

wherein, when predetermined-pitch feeding, by said feed lever, of the  
15 continuous sequin strip has been completed, said lock lever drive  
mechanism causes the engaging claw of said lock lever to engage a center  
hole following the center hole engaged by the hook portion of said feed lever,  
to thereby immovably lock the continuous sequin strip, and

wherein, when said feed lever moves rearward and then moves  
20 forward to again feed the continuous sequin strip, said lock lever drive  
mechanism causes the engaging claw of said lock lever to be disengaged  
from the center hole by such a time when the hook portion of said feed lever  
engages a center hole of another sequin to resume feeding movement of the  
continuous sequin strip.

25

2. A sequin feeding apparatus as claimed in claim 1 wherein said lock  
lever drive mechanism includes means for normally biasing said lock lever  
so that the engaging claw resiliently contacts an upper surface of a sequin

on the supporting plate, and wherein disengagement of the engaging claw of said lock level from the center hole of the sequin is carried out by said feed lever engaging with said lock lever to move the engaging claw, against a biasing force of said biasing means, as said feed lever moves rearward.

5

3. A sequin feeding apparatus as claimed in claim 1 wherein said feeding mechanism supports said feed lever pivotably relative to a pivot arm that is driven to pivot by a motor, and said feed lever is normally biased in a direction where the distal-end hook portion resiliently contacts an upper  
10 surface of a sequin on the supporting plate.

4. A sequin feeding apparatus as claimed in claim 3 wherein said feed lever is normally biased by a spring in a feeding direction thereof, and an output shaft of the motor is placed in a freely-rotatable state after  
15 completion of a feeding cycle.

5. A sequin feeding apparatus as claimed in claim 3 wherein said pivot arm is driven via a link member coupled to an output shaft of the motor.

20 6. A sequin feeding apparatus as claimed in claim 2 wherein said feeding mechanism supports said feed lever pivotably relative to a pivot arm that is driven to pivot by a motor, and said feed lever is normally biased in a direction where the distal-end hook portion resiliently contacts an upper surface of a sequin on the supporting plate.

25

7. A sequin feeding apparatus as claimed in claim 6 wherein said feed lever is normally biased by a spring in a feeding direction thereof, and an output shaft of said motor is placed in a freely-rotatable state upon

completion of a feeding operation cycle.

8. A sequin feeding apparatus as claimed in claim 6 wherein said pivot arm is driven via a link member coupled to an output shaft of the motor.